



KBS STRIP

DIRECTIONS & APPLICATION INFORMATION



KBS Strip, an aircraft strength paint remover sprays as a semi gel coat for fast and easy coverage. This unique semi gel coat results in an even, unbroken film which seals the old surface and allows deep penetration through multiple layers of paint. Due to it's semi gel state, Strip will cling to vertical surfaces with minimal run or sag.

STRIP REMOVES:

Lead-based paints • Polyurethanes • Lacquers
Shellacs • Marine Finishes
Tile & Carpet Adhesives • Epoxies • Latex
Stains • Varnishes • Acrylics • Gas Tank Coatings
Most Any Finish ...

KBS Strip is a heavy-duty paint, stain & varnish remover developed for use on metal, wood & masonry surfaces. This penetrating semi-gel formula clings to vertical surfaces like magic & removes even your toughest finishes fast & easy! The spray bottle applicator promotes even sealing coverage & deep penetrating power for removing stubborn layers of finishes even in hard to reach places! Another advantage of Strip is that it contains an evaporation sealant which drastically lowers the amount of odor. Strip can be easily washed off with water or solvent without leaving a residue.

PROTECTIVE GLOVES AND EYEWEAR SHOULD BE WORN AT ALL TIMES WHEN USING THIS PRODUCT.

DIRECTIONS:

- Carefully pour Strip into spray bottle (use ONLY in special sprayer provided) and adjust the sprayer nozzle for an even spray pattern.
- Spray an even, generous layer of Strip and allow it to work approx. 15 minutes. (heavy coatings may require spraying again to completely loosen surface finish.)
- Gently scrape off blistered finish with putty knife and place in metal container. A small stiff scrub brush can be used on corners or tougher areas.
- After the majority (90%) of the finish is removed, spray again. After 5–10 minutes, wash with #2 steel- wool or stripping pad dipped in water or solvent (paint thinner, alcohol, mineral spirits).
- Wipe completely clean with a rag or paper towel. If not cleaned completely steel wool may leave residue which can cause spots and streaking. Pour unused remover back into container and rinse out both bottle and sprayer with water. Clean up rags, paper and waste promptly. Allow solvents to evaporate, then dispose of in metal container in accordance with local, state and federal regulations.

FOR STRIPPING GAS TANK SEALERS:

- Carefully Pour entire contents of can into tank and slowly rotate and roll tank until all sides are evenly coated. Patiently work with it for a minimum of 20 minutes but no longer than 1 hour, periodically checking inside.

- If an area needs extra attention, prop the tank so that the excess collects on that area. Continue this until the majority of the remaining sealer is loosened and/or removed.
- After Strip has been allowed to work, pour out & capture into an appropriate metal container for possible reuse. Rinse tank thoroughly with water. If any part of the sealer still remains, repeat steps until old sealant is removed.
- Rinse tank with water and allow to dry COMPLETELY before using appropriate prep products and Gold Standard Tank Sealer.

MAY BE HARMFUL TO:

Tile, Linoleum, Asphalt, Plastics, Rubber and Synthetics. If contact occurs, rinse well with water.

NOTE: May soften fiberglass. Strip should be used within six months of opening or disposed of properly to avoid can deterioration.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

Danger: READ ALL CAUTIONS and DIRECTIONS on this container. Vapor harmful. Use only with adequate ventilation to prevent build-up of vapors. Nose and throat irritant. May be harmful if absorbed through skin or inhaled. Harmful if swallowed. Use caution when opening container. Due to variations in temperature, the contents of this can may be under pressure. "Warning: This Product Contains Methylene Chloride Which is known to the state of California to Cause Cancer and Birth Defects or other Reproductive Harm." Methylene Chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. When used frequently on a regular basis, do not exceed appropriate TLV. See MSDS. If possible, use outdoors. Do Not use in areas where vapors can accumulate and concentrate such as basements, bathrooms, or small enclosed areas. If used indoors, open all windows and doors. During application and drying, provide a cross ventilation of moving fresh air across the work area. If strong odor is noticed or if you experience slight dizziness, headache, nausea or eye-watering – STOP – ventilation is inadequate. Leave area immediately. Avoid prolonged or repeated breathing of vapors or spray mist and contact with skin and eyes and clothing. Vapor reduces the blood's oxygen carrying capacity and may cause nose and throat irritation. Wash thoroughly after handling. Use chemical resistant gloves and eye protection to avoid skin contact. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Persons pregnant or thought to have heart or respiratory problems should seek medical advice before using solvents of any kind. When washing residue with flammable solvents such as mineral spirits or lacquer thinner, keep away from heat, sparks and open flame. Shut off pilot lights, stoves heaters, and electric appliances. Vapors may flow along floors, under doors, and on contact with flame or hot surfaces will produce toxic gases and may cause metal corrosion. Do not mix this product with any other remover or liquid. For best results, use in 60 to 85 degree temperatures away from sun and wind. For regular users a properly maintained and properly fitted NIOSH approved self-contained breathing apparatus for chlorinated solvents vapors may offer protection. Obtain professional advice before using. A dust mask does not provide protection against vapors. Close container when not in use and store in a cool place. Exposure to high temperatures or to sun may cause can to swell or leak. Do not reuse this container. FIRST AID – IF SWALLOWED – call your poison control center, hospital emergency room, or physician immediately for instructions. IN CASE OF EYE CONTACT, immediately flush with water for at least 15 minutes. Get medical attention. FOR SKIN CONTACT, wash thoroughly with soap and water. If irritation persists, get immediate medical attention. CONTAINS: Methylene chloride (745-09-2), Methanol (67-56-1), Ethylene glycol butyl ether (111-76-2) which may cause blood damaged based on animal data. DO NOT TAKE INTERNALLY. HARMFUL IF SWALLOWED.

Made in the USA.

Information contained herein is to our knowledge true and accurate, but all recommendations or suggestions are made with out guarantee. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

KBS TECH SUPPORT FORUM

support.KBS-COATINGS.com

KBS HELPDESK

helpdesk.KBS-COATINGS.com